



PARBOND[®] RUBBER SEALANT

Product Overview: PARBOND, manufactured at the PARR facility, is a premium rubber-based sealant that is formulated to provide excellent bonding to any surface. This product is easy to apply in its solvated state, and cures to a tough, flexible bead that provides moisture resistance and weather protection.

Product Uses: PARBOND is well-suited for use in the following applications: miter joints in windows and door frames, needle glazing and top dressing over non-drying sealants, narrow corner joints, and waterproofing. It can also be used to seal gutters, automotive windshields and back lights, sinks, tiles, and ducts.

Technical Information:

Raw Material Base.....Synthetic Polymer	Solids by Weight.....58 – 60%
VOC.....418 g/L	Flash Point.....31°F
Color.....Aluminum, Clear	Tack Free Time (77°F).....30 min.
Specific Gravity.....0.92 – 0.96	Shelf Life.....One Year
Elongation (ASTM D412).....300%	Manufactured State.....Liquid
Tensile Strength.....17 – 19 psi	Odor.....Aromatic Pre-cure, None Post-cure
Viscosity.....30,000 – 50,000 cps	Service Temperature.....-20 – 180°F
Water Resistance.....Excellent	Full Cure Time.....24 – 72 Hours

Application Information: Ensure surfaces to be sealed are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. For best results, apply in a smooth bead and allow to level. Do not handle, move, or pack for one hour until a surface film has formed. If necessary, clean tools and equipment with mineral spirits.

Packaging & Handling: Do not open until ready for use in order to maximize shelf life. Store at 60° – 80°F. Read all labeling before use.

Safety Instructions: WARNING! This product contains toluene, a solvent flammable in both liquid and vaporous states. Keep away from heat, spark, and open flame. Disconnect all gas and electrical appliances near work area. Use in a well ventilated area. Overexposure to vapors may cause dizziness, headache, and unconsciousness. Wear gloves and eye protection. Liquid product is an eye and skin irritant, and is harmful if swallowed. Consult Material Safety Data Sheet for further information.

Contact Us: For more information regarding this product and others, please contact us at:

Edge Adhesives
3200 County Rd. 6 East
Elkhart, IN 46514
www.edgeadhesives.com

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574- 262-9201

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Edge Adhesives control are such that Edge Adhesives assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.

EDGE ADHESIVES BRANDS



PARBOND